



Mailing Address:  
PO Box 1674  
Warsaw, IN 46581-1674

Phone: 844-SEYMOUR  
FAX: 574-267-8508  
[www.seymourmidwest.com](http://www.seymourmidwest.com)

Shipping Address:  
2666 S Country Club Rd  
Warsaw, IN 46580

## Concrete Placer Assembly Instructions

### Tools Needed for Assembly:

- 7/16" wrench (two)

### Parts Shipped with Unit:

- Head
- Handle with T-adapter: aluminum, fiberglass or wood (not shown)
- Bolt Bag for connecting head to handle
- Optional: Hook Hardware Kit, including spare hook

### For Concrete Placer Tool without Optional Hook:

**NOTE:** The T-adapter plate, which is mounted on the handle, is welded at an angle. You may try different positions to determine the angle variation you desire.

1. Align holes on end of handle with EITHER the top or bottom pair of holes on placer head.
2. Insert two shortest bolts and use wrenches to tighten nuts.

### For Concrete Placer Tool with Optional Hook:

**NOTE:** The T-adapter plate, which is mounted on the handle, is welded at an angle. You may try different positions to determine the angle variation you desire.

1. Position head so teardrop edge of head is on top.
2. Align T-adapter with either pair of holes on head.
3. Align holes of hook on head (as shown) and insert appropriate bolts.
4. Use wrenches to tighten all hardware.

#### FULL WARRANTY

*All Seymour Midwest products carry a full warranty against manufacturer defects in quality and workmanship. Products which have been abused or worn out from normal use are excluded from this warranty. We reserve the right to replace or issue credit on an individual basis.*

## REPLACEMENT PARTS LIST

See Reverse Side

PK90179  
1/21/15

## **CONCRETE PLACER REPLACEMENT PARTS**

SP10054	Head-20"
SA20097	Handle w/T-adapter assembly -60" aluminum
SA20144	Handle w/T-adapter assembly -66" aluminum
SA20065	Handle w/T-adapter assembly -60" fiberglass w/ foam grip
SA20087	Handle w/T-adapter assembly -60" wood w/ aluminum sleeve
SA20091	Handle w/ T-adapter assembly- 60" x 1 3/8" aluminum
SA60005	Bolt bag: 3 bolts, 3 loc nuts (for connecting head to handle)
SA60058	Hardware Kit: 2 hooks, 2 bolts, 2 loc nuts
SP50084	Metal cap for aluminum handles #SA20097 & SA20144